

## FLS 692 - Technical Specifications

Material Handling | Solid | | 2 Years

### Salient Features & Benefits

**Forklift Solid FLS 692- Delivers superior stability, durability, and performance in demanding forklift applications.**

#### Wide Tread with Continuous Center Rib

- Broad tread design with a solid central rib.
- Minimizes vibrations, enhances ride comfort, and ensures longer tread life with higher mileage.

#### Optimized Tread Geometry

- Square shoulders with a flat footprint.
- Provides superior stability, improved ground contact, and consistent surface grip for enhanced durability.

#### Advanced Construction and Compound

- Specially engineered casing and high-performance rubber compound.
- Effectively dampens impact and vibration, resists heat build-up, and prevents cracking for extended service life.

#### Steel Wire Creel Beads

- High-strength bead construction.
- Prevents tyre slippage on the rim and minimizes heat generation, ensuring maximum uptime and operational reliability.

#### 3-Stage Construction for Extended Duty Cycles

- Robust 3-layer design built for long working hours.
- Withstands 16–20 hours of continuous operation per day, ideal for demanding industrial and material-handling applications.



## Machineries



Forklift

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	21X8-9 (200/75-9)
Rec Rim	6.00E-09
Wear Limit (mm)	52.5
OW (mm)	183
Overall Diameter (mm)	515
Heel	SH/QH

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Wheel

km/h	
25	2755

### Steer Wheel

km/h	
25	2120