

FLS 692 - Technical Specifications

Material Handling | Solid ||| 2 Years

Salient Features & Benefits

Forklift Solid FLS 692- Delivers superior stability, durability, and performance in demanding forklift applications.

Wide Tread with Continuous Center Rib

- Broad tread design with a solid central rib.
- Minimizes vibrations, enhances ride comfort, and ensures longer tread life with higher mileage.

Optimized Tread Geometry

- Square shoulders with a flat footprint.
- Provides superior stability, improved ground contact, and consistent surface grip for enhanced durability.

Advanced Construction and Compound

- Specially engineered casing and high-performance rubber compound.
- Effectively dampens impact and vibration, resists heat build-up, and prevents cracking for extended service life.

Steel Wire Creel Beads

- High-strength bead construction.
- Prevents tyre slippage on the rim and minimizes heat generation, ensuring maximum uptime and operational reliability.

3-Stage Construction for Extended Duty Cycles

- Robust 3-layer design built for long working hours.
- Withstands 16–20 hours of continuous operation per day, ideal for demanding industrial and material-handling applications.



Machineries



Forklift

Standard: International Standards

Dimensions International Standards

ECE	-
Tyre Size	5.00-8
Rec Rim	3.00D-8
Wear Limit (mm)	43
OW (mm)	118
Overall Diameter (mm)	453
Heel	SH/QH

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Wheel

km/h	
25	1415

Steer Wheel

km/h	
25	1090