

UTR 240 - Technical Specifications

Agriculture | Radial | R-3+ | TL | 7 Years

Salient Features & Benefits

Utility Tractor Radial 240, designed for compact tractor, subcompact tractor

Application Best of R-1, R-4 & Turf in One Tyre:

- Directional Block Tread with Deeper Tread Depth.
- Combines the traction of R-1, toughness of R-4, and minimal ground disturbance of R-3. Delivers high traction on turf, sand, mud, and hard surfaces, with excellent roadability between work sites.

Efficient Fuel Economy with Soil Protection:

- Larger Footprint with More Void & Low Rolling Resistance.
- Protects soil and delicate plants during operation; low rolling resistance reduces fuel consumption, ideal for long working hours or transition runs.

Long-Lasting Performance with Uniform Wear:

- Special Rubber Compound.
- Resists premature wear and provides consistent tread life even on harder surfaces like paved roads or concrete paths.

Turf Friendly with Self-Cleaning Ability:

- Rounded Shoulder Design.
- Minimizes turf damage during turns while offering excellent self-cleaning in soft or wet soils, maintaining traction without compromising the ground.

Built for Versatility and Comfort:

- Radial Construction Optimized for Mixed Service.
- Suitable for small tractors and utility vehicles working in orchards, vineyards, gardens, and municipal applications, ensuring smooth ride comfort and high productivity.



Machineries



Utility Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/21*10025*00
Tyre Size	215/45R10 (18X8.50R10)
Rec Rim	7.00-I-55 X 10
Alternate Rim	-
PR & LI/SI	80A8/B
Section Width (mm)	217
Overall Diameter (mm)	450
Static Load Radius (mm)	208
Rolling Circumference (mm)	1346
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4	2.6
10	560	390	480	560	630	680
15	500	350	430	500	560	600
25	410	290	360	410	470	500
30	400	280	340	400	450	480
40	370	260	320	370	420	450
50	370	260	320	370	420	450
Static	850	600	740	850	970	1040