



## UTR 240 - Technical Specifications

Agriculture | Radial | R-3+ | TL | 7 Years

### Salient Features & Benefits

#### Utility Tractor Radial 240, designed for compact tractor, subcompact tractor

##### Application Best of R-1, R-4 & Turf in One Tyre:

- Directional Block Tread with Deeper Tread Depth.
- Combines the traction of R-1, toughness of R-4, and minimal ground disturbance of R-3. Delivers high traction on turf, sand, mud, and hard surfaces, with excellent roadability between work sites.

##### Efficient Fuel Economy with Soil Protection:

- Larger Footprint with More Void & Low Rolling Resistance.
- Protects soil and delicate plants during operation; low rolling resistance reduces fuel consumption, ideal for long working hours or transition runs.

##### Long-Lasting Performance with Uniform Wear:

- Special Rubber Compound.
- Resists premature wear and provides consistent tread life even on harder surfaces like paved roads or concrete paths.

##### Turf Friendly with Self-Cleaning Ability:

- Rounded Shoulder Design.
- Minimizes turf damage during turns while offering excellent self-cleaning in soft or wet soils, maintaining traction without compromising the ground.

##### Built for Versatility and Comfort:

- Radial Construction Optimized for Mixed Service.
- Suitable for small tractors and utility vehicles working in orchards, vineyards, gardens, and municipal applications, ensuring smooth ride comfort and high productivity.



## Machineries



Utility Tractor

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	E11*106R00/21*11227*00
Tyre Size	215/50R10
Rec Rim	7.00-I_x0002_55 X 10
Alternate Rim	-
PR & LI/SI	80A8/B
Section Width (mm)	217
Overall Diameter (mm)	469
Static Load Radius (mm)	216
Rolling Circumference (mm)	1403
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	0.8	1.2	1.6	2	2.4	2.6
10	330	420	510	600	680	680
15	290	380	460	540	600	600
25	240	310	380	440	500	500
30	240	300	360	430	480	480
40	220	280	340	400	450	450
50	220	280	340	400	450	450
Static	510	640	780	920	1040	1040