

UTR 240 - Technical Specifications

Agriculture | Radial | R-3+ | TL | 7 Years

Salient Features & Benefits

Utility Tractor Radial 240, designed for compact tractor, subcompact tractor

Application Best of R-1, R-4 & Turf in One Tyre:

- Directional Block Tread with Deeper Tread Depth.
- Combines the traction of R-1, toughness of R-4, and minimal ground disturbance of R-3. Delivers high traction on turf, sand, mud, and hard surfaces, with excellent roadability between work sites.

Efficient Fuel Economy with Soil Protection:

- Larger Footprint with More Void & Low Rolling Resistance.
- Protects soil and delicate plants during operation; low rolling resistance reduces fuel consumption, ideal for long working hours or transition runs.

Long-Lasting Performance with Uniform Wear:

- Special Rubber Compound.
- Resists premature wear and provides consistent tread life even on harder surfaces like paved roads or concrete paths.

Turf Friendly with Self-Cleaning Ability:

- Rounded Shoulder Design.
- Minimizes turf damage during turns while offering excellent self-cleaning in soft or wet soils, maintaining traction without compromising the ground.

Built for Versatility and Comfort:

- Radial Construction Optimized for Mixed Service.
- Suitable for small tractors and utility vehicles working in orchards, vineyards, gardens, and municipal applications, ensuring smooth ride comfort and high productivity.



Machineries



Utility Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*7132*00
Tyre Size	220/55R12
Rec Rim	7.00B / 7.00-I-90
Alternate Rim	-
PR & LI/SI	82A8/B
Section Width (mm)	220
Overall Diameter (mm)	550
Static Load Radius (mm)	254
Rolling Circumference (mm)	1645
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	0.8	1.2	1.6	1.9
10	410	510	630	710
15	-	-	-	-
25	300	380	470	530
30	290	360	450	510
40	270	340	420	475
50	270	340	420	475
Static	620	780	970	1090