

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action

- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/19*7326*00
Tyre Size	5.00-15
Rec Rim	3.50D
Alternate Rim	-
PR & LI/SI	6 PR 88 A8 FR 75 A8 DW
Section Width (mm)	130
Overall Diameter (mm)	655
Static Load Radius (mm)	304
Rolling Circumference (mm)	1959
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.7	2.9	3.2	3.5
10	480	490	520	540
25	400	420	440	460
40	340	350	370	387
50	306	320	330	350

Free rolling

km/h / bar	2.7	2.9	3.2	3.5
10	670	700	740	780
25	570	600	630	670
40	480	500	530	560
50	430	450	480	500