

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action

- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6532*00
Tyre Size	10.0/75-15.3
Rec Rim	9
Alternate Rim	-
PR & LI/SI	10 PR 123 A8 FR 111 A8 DW
Section Width (mm)	264
Overall Diameter (mm)	780
Static Load Radius (mm)	356
Rolling Circumference (mm)	2333
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	3	3.3	3.6	3.9
10	1320	1390	1460	1530
25	1120	1180	1240	1300
40	940	990	1040	1090
50	846	891	936	981

Free rolling

km/h / bar	3	3.3	3.6	3.9
10	1860	1970	2070	2170
25	1580	1680	1760	1840
40	1330	1410	1480	1550
50	1200	1270	1330	1400