

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action


- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6545*00
Tyre Size	11.5/80-15.3
Rec Rim	9
Alternate Rim	-
PR & LI/SI	12 PR 135 A8 FR 123 A8 DW
Section Width (mm)	290
Overall Diameter (mm)	867
Static Load Radius (mm)	392
Rolling Circumference (mm)	2594
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	3.1	3.4	3.7	4.1
10	1850	1950	2040	2170
25	1570	1650	1740	1840
40	1320	1390	1460	1550
50	1188	1251	1314	1395

Free rolling

km/h / bar	3.1	3.4	3.7	4.1
10	2590	2730	2870	3050
25	2200	2320	2440	2590
40	1850	1950	2050	2180
50	1670	1760	1850	1960