

## IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

### Salient Features & Benefits

### IMB 162, specially designed for implements

#### High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

#### Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

#### Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

#### Strong Grip with Self-Cleaning Action


- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

#### Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



## Machineries



**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*7325*00
Tyre Size	6.00-16
Rec Rim	4.00E
Alternate Rim	-
PR & LI/SI	8 PR 103 A8 FR 91 A8 DW
Section Width (mm)	160
Overall Diameter (mm)	730
Static Load Radius (mm)	337
Rolling Circumference (mm)	2183
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Drive Wheel

km/h / bar	2.9	3.2	3.6	4
10	710	760	810	860
25	610	640	690	730
40	510	540	580	615
50	459	490	520	550

### Free rolling

km/h / bar	2.9	3.2	3.6	4
10	1020	1080	1150	1230
25	870	920	980	1040
40	730	770	820	875
50	660	690	740	790