

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action


- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*8105*00
Tyre Size	6.50-16
Rec Rim	4.5KA 4.5KB
Alternate Rim	-
PR & LI/SI	8PR 105 A8 FR 93 A8 DW
Section Width (mm)	175
Overall Diameter (mm)	760
Static Load Radius (mm)	349
Rolling Circumference (mm)	2273
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.8	3.1	3.4	3.7
10	780	830	870	910
25	670	700	740	770
40	560	590	620	650
50	504	530	560	590

Free rolling

km/h / bar	2.8	3.1	3.4	3.7
10	1090	1160	1230	1300
25	930	990	1050	1100
40	780	830	880	925
50	700	750	790	830