



MIB 407 - Technical Specifications

Industrial & Construction | Bias | IND | TL | 5 Years

Salient Features & Benefits

Multi Industrial Bias 407, specially designed for telehandler, grader and compact wheel loader applications.

Maximum Protection in Demanding Conditions

- Extra-wide sidewall design
- Provides high puncture and impact resistance, shielding the tyre from external hazards, ideal for rough, debris-prone job sites.

Exceptional Ground Stability & Ride Control

- Reinforced Sidewall Construction
- Enhances lateral stability during load shifts and machine movement, minimizing sway or bounce in compact machinery operations.

Engineered for Heavy Loads

- Enhanced Carcass with High Ply Rating
- Supports high load-carrying capacity while maintaining structural integrity under tough duty cycles.

Built for Longevity & Traction

- Directional Tread with Strong Lugs
- Offers superior grip on loose, rocky, or uneven ground with uniform wear, contributing to extended tyre life and consistent performance.



Machineries



Backhoe Loader



Compact Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*10456*00
Tyre Size	18-22.5 (445/65-22.5)
Rec Rim	14
Alternate Rim	-
PR & LI/SI	16PR 164A8
Section Width (mm)	457
Overall Diameter (mm)	1172
Static Load Radius (mm)	533
Rolling Circumference (mm)	3505
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	5.9	7.5
Static	11500	13340

Mixed Application

km/h / bar	5.9	7.5
10	6250	7250
25	5300	6150
30	5200	6030
40	5000	5800

Cylic

km/h / bar	5.9	7.5
10	7500	8700