



## TSB 111 - Technical Specifications

Agriculture | Bias | F-2 | TT | 5 Years



### Salient Features & Benefits

**Tractor Steer Bias 111 specially design for Tractors.**

#### Excellent Steering performance

- Unique Dumbbell Pattern.
- Suitable to use in soil tillage and haulage applications.

#### High Mileage

- Higher read depth.
- Longer tyre Life.

#### High Load Carrying Capacity

- Strong Nylon Casing.
- With stand high load in service.

#### Excellent Durability

- High-performance Tread compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*7026*00
Tyre Size	5.50-16
Rec Rim	4.00E
Alternate Rim	3.50D, 4.50E
PR & LI/SI	6PR 82 A8
Section Width (mm)	150
Overall Diameter (mm)	713
Static Load Radius (mm)	330
Rolling Circumference (mm)	2133
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	2.2	2.6	3	3.9
Static	1020	1140	1230	1430

### Mixed Application

km/h / bar	2.2	2.6	3	3.9
10	680	760	820	950
20	470	520	560	650
25	440	490	520	610
30	380	420	460	530
40	340	380	410	475