



## TSB 111 - Technical Specifications

Agriculture | Bias | F-2 | TT | 5 Years



### Salient Features & Benefits

**Tractor Steer Bias 111 specially design for Tractors.**

#### Excellent Steering performance

- Unique Dumbbell Pattern.
- Suitable to use in soil tillage and haulage applications.

#### High Mileage

- Higher read depth.
- Longer tyre Life.

#### High Load Carrying Capacity

- Strong Nylon Casing.
- With stand high load in service.

#### Excellent Durability

- High-performance Tread compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/19*6787*00
Tyre Size	6.00-16
Rec Rim	4.50E
Alternate Rim	4.00E, 5.00F, 5K
PR & LI/SI	8 PR 91 A8
Section Width (mm)	165
Overall Diameter (mm)	739
Static Load Radius (mm)	340
Rolling Circumference (mm)	2210
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	3.4	3.7	4.1	4.5
Static	1560	1650	1740	1850

### Mixed Application

km/h / bar	3.4	3.7	4.1	4.5
10	1040	1100	1160	1230
20	720	760	800	850
25	670	700	740	790
30	580	610	640	680
40	520	550	580	615