

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action


- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7328*00
Tyre Size	7.50-18
Rec Rim	5.50F
Alternate Rim	-
PR & LI/SI	8 PR 114 A8 FR 101 A8 DW
Section Width (mm)	209
Overall Diameter (mm)	854
Static Load Radius (mm)	392
Rolling Circumference (mm)	2554
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.4	2.6	2.8	3.1
10	1010	1050	1090	1160
25	860	890	930	980
40	720	750	780	825
50	648	680	700	740

Free rolling

km/h / bar	2.4	2.6	2.8	3.1
10	1410	1480	1550	1650
25	1200	1260	1320	1400
40	1010	1060	1110	1180
50	910	950	1000	1060