



## TSB 111 - Technical Specifications

Agriculture | Bias | F-2 | TT | 5 Years



### Salient Features & Benefits

**Tractor Steer Bias 111 specially design for Tractors.**

#### Excellent Steering performance

- Unique Dumbbell Pattern.
- Suitable to use in soil tillage and haulage applications.

#### High Mileage

- Higher read depth.
- Longer tyre Life.

#### High Load Carrying Capacity

- Strong Nylon Casing.
- With stand high load in service.

#### Excellent Durability

- High-performance Tread compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

|                            |                       |
|----------------------------|-----------------------|
| ECE                        | E11*106R00/17*6851*00 |
| Tyre Size                  | 6.00-19               |
| Rec Rim                    | 4.5E                  |
| Alternate Rim              | 4.00E                 |
| PR & LI/SI                 | 8 PR 91 A8            |
| Section Width (mm)         | 165                   |
| Overall Diameter (mm)      | 814                   |
| Static Load Radius (mm)    | 376                   |
| Rolling Circumference (mm) | 2435                  |
| Type                       | TT                    |

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

| km/h / bar | 2.9  | 3.2  | 3.5  | 3.9  |
|------------|------|------|------|------|
| Static     | 1560 | 1650 | 1740 | 1850 |

### Mixed Application

| km/h / bar | 2.9  | 3.2  | 3.5  | 3.9  |
|------------|------|------|------|------|
| 10         | 1040 | 1100 | 1160 | 1230 |
| 20         | 720  | 760  | 800  | 850  |
| 25         | 670  | 700  | 740  | 790  |
| 30         | 580  | 610  | 640  | 680  |
| 40         | 520  | 550  | 580  | 615  |