

IMB 162 - Technical Specifications

Agriculture | Bias | I-3 | TT/TL | 5 Years

Salient Features & Benefits

IMB 162, specially designed for implements

High Load Carrying Capacity

- Reinforced nylon carcass
- Withstands high load during field operations and transport, ensuring long-lasting performance

Low Soil Protection

- Wider contact patch with optimised tread geometry
- Minimises soil compaction and safeguards soil health in sensitive agricultural conditions

Excellent Road ability

- Directional tread pattern with balanced lug design
- Provides a smooth and stable ride on both road and field surfaces

Strong Grip with Self-Cleaning Action


- Directional tread design with open lugs
- Provides improved traction in soft or tilled soil and ejects mud for uninterrupted performance

Excellent Durability

- Cut & Chip resistant Tread Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life.



Machineries



Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7327*00
Tyre Size	7.50-20
Rec Rim	5.50F
Alternate Rim	-
PR & LI/SI	8 PR 116 A8 FR 103 A8 DW
Section Width (mm)	209
Overall Diameter (mm)	904
Static Load Radius (mm)	417
Rolling Circumference (mm)	2704
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Drive Wheel

km/h / bar	2.5	2.7	3	3.25
10	1050	1090	1160	1230
25	890	930	990	1040
40	750	780	830	875
50	675	700	750	790

Free rolling

km/h / bar	2.5	2.7	3	3.25
10	1500	1570	1670	1750
25	1270	1330	1420	1490
40	1070	1120	1190	1250
50	960	1010	1070	1130