

## TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 120, specially designed for tractors in soil tillage applications**

#### Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

#### Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	250/80-18
Rec Rim	8
Alternate Rim	-
PR & LI/SI	8 PR 117 A8
Section Width (mm)	251
Overall Diameter (mm)	870
Static Load Radius (mm)	399
Rolling Circumference (mm)	2602
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field application with high torque

km/h / bar	2.8
10HT	1370

### Field application with Low torque

km/h / bar	2.8
10HT	1930
20HT	1580

### Road Operation Not high and Sustained Torque

km/h / bar	2.8
10	1930
20	1580
30	1370
40	1285
Static	2960