

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*10062*00 (TL)
Tyre Size	8.3-24
Rec Rim	W7
Alternate Rim	-
PR & LI/SI	8 PR 105 A8
Section Width (mm)	211
Overall Diameter (mm)	993
Static Load Radius (mm)	463
Rolling Circumference (mm)	2970
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	1.7	2.5	2.8	3.1
10HT	700	870	930	990

Field application with Low torque

km/h / bar	1.7	2.5	2.8	3.1
10HT	980	1220	1310	1390
20HT	800	1000	1070	1140

Road Operation Not high and Sustained Torque

km/h / bar	1.7	2.5	2.8	3.1
10	980	1220	1310	1390
20	800	1000	1070	1140
30	700	870	930	990
40	650	810	870	925
Static	1500	1860	2000	2130