

## TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 120, specially designed for tractors in soil tillage applications**

#### Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

#### Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/18*6514*00
Tyre Size	9.5-24
Rec Rim	W8
Alternate Rim	W7, W8H
PR & LI/SI	8 PR 112 A8
Section Width (mm)	241
Overall Diameter (mm)	1048
Static Load Radius (mm)	486
Rolling Circumference (mm)	3135
Type	TT/TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field application with high torque

km/h / bar	2.3	2.5	2.8
10HT	1070	1120	1200

### Field application with Low torque

km/h / bar	2.3	2.5	2.8
10HT	1500	1580	1680
20HT	1230	1290	1380

### Road Operation Not high and Sustained Torque

km/h / bar	2.3	2.5	2.8
10	1500	1580	1680
20	1230	1290	1380
30	1070	1120	1200
40	1000	1050	1120
Static	2300	2420	2580