

## TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 120, specially designed for tractors in soil tillage applications**

#### Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

#### Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/18*6519*00(TT) E11*106R00/20*10057*00(TL)
Tyre Size	11.2-24
Rec Rim	W10
Alternate Rim	W9, W10H
PR & LI/SI	8 PR 116 A8
Section Width (mm)	284
Overall Diameter (mm)	1103
Static Load Radius (mm)	509
Rolling Circumference (mm)	3299
Type	TT/TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field application with high torque

km/h / bar	2	2.2	2.5
10HT	1180	1240	1340

### Field application with Low torque

km/h / bar	2	2.2	2.5
10HT	1650	1740	1880
20HT	1350	1430	1540

### Road Operation Not high and Sustained Torque

km/h / bar	2	2.2	2.5
10	1650	1740	1880
20	1350	1430	1540
30	1180	1240	1340
40	1100	1160	1250
Static	2530	2670	2880