

## TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 120, specially designed for tractors in soil tillage applications**

#### Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

#### Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	12.4-24
Rec Rim	W11
Alternate Rim	W10, W10H
PR & LI/SI	12 PR 128 A8
Section Width (mm)	315
Overall Diameter (mm)	1159
Static Load Radius (mm)	532
Rolling Circumference (mm)	3467
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field application with high torque

km/h / bar	2.8	3.2	3.4
10HT	1720	1860	1930

### Field application with Low torque

km/h / bar	2.8	3.2	3.4
10HT	2420	2610	2700
20HT	1980	2140	2210

### Road Operation Not high and Sustained Torque

km/h / bar	2.8	3.2	3.4
10	2420	2610	2700
20	1980	2140	2210
30	1720	1860	1930
40	1610	1740	1800
Static	3700	4000	4140