



## AFB 821 - Technical Specifications

Forestry | Bias | R-1 | TL | 5 Years



### Salient Features & Benefits

**AFB 821 Engineered for dependable use in forestry, mulching, and field tasks.**

#### Heavy-Duty Traction

- Sharp-edged lug design with deeper tread bars
- Delivers powerful grip even on wet, loose, and uneven terrain

#### Stability in Field and Forest

- Flat and wide tread footprint
- Ensures balance and consistent ground contact for safe handling on slopes and rough terrain

#### Puncture and Cut Resistance

- Special forestry compound with reinforced steel belts
- Resists stubble, cut, and chip damage for longer tyre life in aggressive terrain

#### Self-Cleaning Lug Design

- Wide lug spacing with debris ejection grooves
- Prevents mud buildup and maintains traction in forest soil conditions

## Machineries



Forestry Tractor

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	E11*106R00/19*7979*00
Tyre Size	14.9-24 (SB)
Rec Rim	W13
Alternate Rim	-
PR & LI/SI	16PR 140 A8
Section Width (mm)	378
Overall Diameter (mm)	1265
Static Load Radius (mm)	575
Rolling Circumference (mm)	3799
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Mixed Application

km/h / bar	2.8
10	3750
25	3080
30	2680
40	2500