



AFB 820 - Technical Specifications

Forestry | Bias | R-1 | TL | 5 Years

Salient Features & Benefits

AFB 820 Agro Forestry tyre Ideal for multipurpose tractors and forestry work.

High Traction in Tough Terrain

- Robust lug geometry with deeper tread and shoulder ridges
- Delivers superior grip and reduced slippage on uneven, wet or loose forest floors

Superior Stability & Load Handling

- Flat and wide tread profile with reinforced casing
- Ensures better ground contact and consistent balance during forestry or agricultural use

Extended Tyre Life

- Special forestry-grade tread compound
- Resists cuts, chips and tread wear from stumps, stones, and sharp objects

Self-Cleaning for Continuous Operation

- Optimized Lug spacing
- Ejects mud and debris, ensuring uninterrupted traction and clean tread



Machineries



Forestry Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/19*7102*00
Tyre Size	18.4-26
Rec Rim	16
Alternate Rim	W15L, DW16A
PR & LI/SI	16 PR 156 A8
Section Width (mm)	467
Overall Diameter (mm)	1450
Static Load Radius (mm)	656
Rolling Circumference (mm)	4337
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Mixed Application

km/h / bar	2.5
10	6000
25	4920
30	4280
40	4000