

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6520*00 (TT) E11*106R00/20*10064*00(TL)
Tyre Size	11.2-28
Rec Rim	W10
Alternate Rim	W9, W10H
PR & LI/SI	8 PR 118 A8
Section Width (mm)	284
Overall Diameter (mm)	1205
Static Load Radius (mm)	560
Rolling Circumference (mm)	3604
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	2	2.2	2.5
10HT	1230	1310	1410

Field application with Low torque

km/h / bar	2	2.2	2.5
10HT	1730	1830	1980
20HT	1410	1500	1620

Road Operation Not high and Sustained Torque

km/h / bar	2	2.2	2.5
10	1730	1830	1980
20	1410	1500	1620
30	1230	1310	1410
40	1150	1220	1320
Static	2650	2810	3040