

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7029*00
Tyre Size	16.9-26
Rec Rim	W15L
Alternate Rim	DW14A, DW15A
PR & LI/SI	10 PR 133 A8
Section Width (mm)	429
Overall Diameter (mm)	1384
Static Load Radius (mm)	629
Rolling Circumference (mm)	4140
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	1.6	1.7	1.8	1.9
10HT	1990	2070	2140	2200

Field application with Low torque

km/h / bar	1.6	1.7	1.8	1.9
10HT	2790	2900	3000	3090
20HT	2290	2370	2460	2530

Road Operation Not high and Sustained Torque

km/h / bar	1.6	1.7	1.8	1.9
10	2790	2900	3000	3090
20	2290	2370	2460	2530
30	1990	2070	2140	2200
40	1860	1930	2000	2060
Static	4280	4440	4600	4740