

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6524*00(TT) E11*106R00/21*10067*00(TL)
Tyre Size	16.9-28
Rec Rim	W15L
Alternate Rim	W14L
PR & LI/SI	8 PR 135 A8
Section Width (mm)	429
Overall Diameter (mm)	1435
Static Load Radius (mm)	655
Rolling Circumference (mm)	4292
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	1.7	2
10HT	2200	2330

Field application with Low torque

km/h / bar	1.7	2
10HT	3090	3270
20HT	2530	2680

Road Operation Not high and Sustained Torque

km/h / bar	1.7	2
10	3090	3270
20	2530	2680
30	2200	2330
40	2060	2180
Static	4740	5010