

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/18*6542*00(TT) E11*106R00/20*10074*00(TL)
Tyre Size	16.9-34
Rec Rim	W15L
Alternate Rim	DW14A
PR & LI/SI	8 PR 139 A8
Section Width (mm)	429
Overall Diameter (mm)	1587
Static Load Radius (mm)	731
Rolling Circumference (mm)	4747
Type	TT/TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	1.5	1.7
10HT	2460	2600

Field application with Low torque

km/h / bar	1.5	1.7
10HT	3450	3650
20HT	2830	2990

Road Operation Not high and Sustained Torque

km/h / bar	1.5	1.7
10	3450	3650
20	2830	2990
30	2460	2600
40	2300	2430
Static	5290	5590