



AFB 821 - Technical Specifications

Forestry | Bias | R-1 | TL | 5 Years



Salient Features & Benefits

AFB 821 Engineered for dependable use in forestry, mulching, and field tasks.

Heavy-Duty Traction

- Sharp-edged lug design with deeper tread bars
- Delivers powerful grip even on wet, loose, and uneven terrain

Stability in Field and Forest

- Flat and wide tread footprint
- Ensures balance and consistent ground contact for safe handling on slopes and rough terrain

Puncture and Cut Resistance

- Special forestry compound with reinforced steel belts
- Resists stubble, cut, and chip damage for longer tyre life in aggressive terrain

Self-Cleaning Lug Design

- Wide lug spacing with debris ejection grooves
- Prevents mud buildup and maintains traction in forest soil conditions

Machineries



Forestry Tractor

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/21*7982*00
Tyre Size	16.9-34 (SB)
Rec Rim	W15L
Alternate Rim	-
PR & LI/SI	16PR 151 A8
Section Width (mm)	429
Overall Diameter (mm)	1587
Static Load Radius (mm)	730
Rolling Circumference (mm)	4766
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Mixed Application

km/h / bar	2.8
10	5180
25	4240
30	3690
40	3450