

## TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



### Salient Features & Benefits

**Tractor Drive Bias 120, specially designed for tractors in soil tillage applications**

#### Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

#### Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

#### Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

#### Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

## Machineries



Tractor

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/18*6527*00
Tyre Size	12.4-36
Rec Rim	W11L
Alternate Rim	W10H,W10
PR & LI/SI	8 PR 126 A8
Section Width (mm)	315
Overall Diameter (mm)	1464
Static Load Radius (mm)	684
Rolling Circumference (mm)	4379
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Field application with high torque

km/h / bar	1.9	2.1	2.2
10HT	1670	1770	1820

### Field application with Low torque

km/h / bar	1.9	2.1	2.2
10HT	2340	2480	2550
20HT	1920	2030	2090

### Road Operation Not high and Sustained Torque

km/h / bar	1.9	2.1	2.2
10	2340	2480	2550
20	1920	2030	2090
30	1670	1770	1820
40	1560	1650	1700
Static	3590	3800	3910