

TDB 120 - Technical Specifications

Agriculture | Bias | R-1 | TT/TL | 5 Years



Salient Features & Benefits

Tractor Drive Bias 120, specially designed for tractors in soil tillage applications

Enhances Traction

- Design with 45 deg Multiangled lugs.
- Provides Excellent Grip & excellent Self-cleaning properties.

Ensures a comfortable ride

- Wider lugs.
- Less soil compaction with a smooth ride

Safeguards the tyre against failures

- Reinforced casing.
- Resistance to impact, mechanical failure & extended tyre life.

Durability

- Sturdy Sidewall Structure
- Provides resistance to external damage

Machineries



Tractor

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/19*7747*00
Tyre Size	13.6-36
Rec Rim	W12
Alternate Rim	W11
PR & LI/SI	8 PR 129 A8
Section Width (mm)	345
Overall Diameter (mm)	1514
Static Load Radius (mm)	705
Rolling Circumference (mm)	4529
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Field application with high torque

km/h / bar	1.7	1.8	1.9
10HT	1850	1920	1980

Field application with Low torque

km/h / bar	1.7	1.8	1.9
10HT	2600	2690	2780
20HT	2130	2200	2280

Road Operation Not high and Sustained Torque

km/h / bar	1.7	1.8	1.9
10	2600	2690	2780
20	2130	2200	2280
30	1850	1920	1980
40	1730	1790	1850
Static	3980	4120	4260