



FLB 680 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years

Salient Features & Benefits

Forklift Bias 680 tyres, specially designed for forklift vehicles in port / industrial applications.

Confident Grip Across Applications

- Precision-Engineered Block Pattern
- Delivers strong traction and directional control, essential for safe handling in varied material movement tasks.

Superior Stability and Load-Carrying Capacity:

- Wide Footprint and Optimum Load Distribution.
- The wide tread profile enhances stability and load-bearing capacity, ideal for forklift and material handling operations.

Performance Across All Environments:

- Versatile Design for Indoor and Outdoor Use.
- Delivers exceptional performance whether operating indoors on smooth surfaces or outdoors on rougher terrain, ensuring versatile usability.



Machineries



Forklift

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*7619*00
Tyre Size	6.00-9
Rec Rim	4.00EX9
Alternate Rim	-
PR & LI/SI	12PR
Section Width (mm)	160
Overall Diameter (mm)	545
Static Load Radius (mm)	245
Rolling Circumference (mm)	1630
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Wheel

km/h / bar	10
15	1875

Steer Wheel

km/h / bar	10
25	1425