



FLB 680 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years

Salient Features & Benefits

Forklift Bias 680 tyres, specially designed for forklift vehicles in port / industrial applications.



Confident Grip Across Applications

- Precision-Engineered Block Pattern
- Delivers strong traction and directional control, essential for safe handling in varied material movement tasks.

Superior Stability and Load-Carrying Capacity:

- Wide Footprint and Optimum Load Distribution.
- The wide tread profile enhances stability and load-bearing capacity, ideal for forklift and material handling operations.

Performance Across All Environments:

- Versatile Design for Indoor and Outdoor Use.
- Delivers exceptional performance whether operating indoors on smooth surfaces or outdoors on rougher terrain, ensuring versatile usability.

Machineries



Forklift

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	7.00-12
Rec Rim	5.00SX12
Alternate Rim	-
PR & LI/SI	14PR
Section Width (mm)	192
Overall Diameter (mm)	683
Static Load Radius (mm)	308
Rolling Circumference (mm)	2042
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Wheel

km/h / bar	9
15	2790

Steer Wheel

km/h / bar	9
25	2120