

FLB 681 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years



Salient Features & Benefits

Forklift Bias 681 tyres, specially designed for forklift vehicles in port / industrial for heavy-duty applications

Optimized Load Distribution and Stability:

- Specially Designed Tread.
- Ensures optimum load distribution with a wide footprint, providing enhanced stability, especially in demanding industrial forklift operations.

Superior Durability and Protection:

- Unique Block Pattern.
- Offers resistance against abrasions, punctures, and impacts, ensuring reliable performance and reducing downtime in heavy-duty environments.

High Load-Capacity Construction:

- Strong Casing.
- Built for high load-bearing applications, offering excellent durability and stability, even under challenging conditions.

Machineries



Forklift

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	32x12.1-15 (HD)
Rec Rim	9.75
Alternate Rim	-
PR & LI/SI	24PR 169A6
Section Width (mm)	305
Overall Diameter (mm)	811
Static Load Radius (mm)	368
Rolling Circumference (mm)	2426
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Wheel

km/h / bar	10
30	7566

Steer Wheel

km/h / bar	10
30	5820