



## FLB 680 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years

### Salient Features & Benefits

**Forklift Bias 680 tyres, specially designed for forklift vehicles in port / industrial applications.**



### Confident Grip Across Applications

- Precision-Engineered Block Pattern
- Delivers strong traction and directional control, essential for safe handling in varied material movement tasks.

### Superior Stability and Load-Carrying Capacity:

- Wide Footprint and Optimum Load Distribution.
- The wide tread profile enhances stability and load-bearing capacity, ideal for forklift and material handling operations.

### Performance Across All Environments:

- Versatile Design for Indoor and Outdoor Use.
- Delivers exceptional performance whether operating indoors on smooth surfaces or outdoors on rougher terrain, ensuring versatile usability.

## Machineries



Forklift

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	300-15
Rec Rim	8.0X15
Alternate Rim	-
PR & LI/SI	20PR
Section Width (mm)	300
Overall Diameter (mm)	840
Static Load Radius (mm)	380
Rolling Circumference (mm)	2512
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Wheel

km/h / bar	9.3
15	6575

### Steer Wheel

km/h / bar	9.3
25	4990