

## FLB 681 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years



### Salient Features & Benefits

**Forklift Bias 681 tyres, specially designed for forklift vehicles in port / industrial for heavy-duty applications**

#### Optimized Load Distribution and Stability:

- Specially Designed Tread.
- Ensures optimum load distribution with a wide footprint, providing enhanced stability, especially in demanding industrial forklift operations.

#### Superior Durability and Protection:

- Unique Block Pattern.
- Offers resistance against abrasions, punctures, and impacts, ensuring reliable performance and reducing downtime in heavy-duty environments.

#### High Load-Capacity Construction:

- Strong Casing.
- Built for high load-bearing applications, offering excellent durability and stability, even under challenging conditions.

## Machineries



Forklift

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	9.00-20 (HD)
Rec Rim	7
Alternate Rim	-
PR & LI/SI	16PR
Section Width (mm)	269
Overall Diameter (mm)	1036
Static Load Radius (mm)	472
Rolling Circumference (mm)	3098
Type	TT

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Wheel

km/h / bar	10
25	6175

### Steer Wheel

km/h / bar	10
25	4750