



FLB 681 - Technical Specifications

Material Handling | Bias | NHS | TT | 5 Years



Salient Features & Benefits

Forklift Bias 681 tyres, specially designed for forklift vehicles in port / industrial for heavy-duty applications

Optimized Load Distribution and Stability:

- Specially Designed Tread.
- Ensures optimum load distribution with a wide footprint, providing enhanced stability, especially in demanding industrial forklift operations.

Superior Durability and Protection:

- Unique Block Pattern.
- Offers resistance against abrasions, punctures, and impacts, ensuring reliable performance and reducing downtime in heavy-duty environments.

High Load-Capacity Construction:

- Strong Casing.
- Built for high load-bearing applications, offering excellent durability and stability, even under challenging conditions.

Machineries



Forklift

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	12.00-20 (HD)
Rec Rim	8.5
Alternate Rim	-
PR & LI/SI	20PR
Section Width (mm)	315
Overall Diameter (mm)	1146
Static Load Radius (mm)	517
Rolling Circumference (mm)	3427
Type	TT

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Wheel

km/h / bar	10
25	9230

Steer Wheel

km/h / bar	10
25	7100