



SSB 333 - Technical Specifications

Industrial & Construction | Bias | NHS | TL | 5 Years

Salient Features & Benefits

Skid Steer Bias 333, specially designed for skid steer used in all terrain

Superior Traction on Rough Surfaces:

- High Tread Depth, Broad Lugs, and Special Compound.
- Optimized for use on hard and rough surfaces, providing superior traction and performance in challenging environments.

High Durability and Puncture Protection:

- Robust Casing.
- Offers exceptional durability, safeguarding against punctures and other damages, even in demanding conditions.

Rim and Wheel Protection:

- Rim Guard.
- Protects the rim flange area against flats and wheel damage, extending the service life of both the tyre and the wheel.



Machineries



Skid Steer Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/19*7435*00
Tyre Size	10-16.5
Rec Rim	8.25
Alternate Rim	-
PR & LI/SI	10PR 134A2
Section Width (mm)	264
Overall Diameter (mm)	773
Static Load Radius (mm)	356
Rolling Circumference (mm)	2312
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar		5.2
10		2130
30		1440