

SSB 332 - Technical Specifications

Industrial & Construction | Bias | NHS (L-5) | TL | 5 Years

Salient Features & Benefits

Skid Steer Bias 332, specially designed for skid steer

Superior Traction and Extended Life:

- Extra Deep Tread Depth.
- Delivers exceptional traction in challenging conditions while providing long-lasting performance for extended service hours.

High Stability and Puncture Resistance:

- Wider and Sturdier Blocks.
- Ensures high stability and reduces the risk of punctures, improving operational safety and uptime.

Enhanced Durability in Severe Conditions:

- Advanced Tread Compound.
- Offers excellent wear resistance, minimizing the effects of severe operating environments and extending the tyre life.

Rim and Wheel Protection:

- Reinforced Rim Guard.
- Protects against flats and wheel damage, ensuring tyre integrity and reducing the risk of costly repairs.



Machineries



Skid Steer Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/18*6866*00
Tyre Size	12-16.5
Rec Rim	9.75
Alternate Rim	-
PR & LI/SI	12PR 145A2
Section Width (mm)	307
Overall Diameter (mm)	831
Static Load Radius (mm)	380
Rolling Circumference (mm)	2486
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar		5.5
10		2900
30		1970