



## GLT 2100 - Technical Specifications

Earth Mover | All Steel Radial | G-2/L-2 | TL | 5 Years

### Salient Features & Benefits

**GLT 2100 Grader Loader Radial is an All-Steel Radial construction Tyre specially designed for Grading & Loading Application.**

**Aggressive Non-Directional Tread Deep multi-block pattern with wide, self-cleaning grooves:**

- Generates powerful traction in mud, loose soil, and wet terrain while shedding debris to maintain grip and slow wear.

**Self-cleaning Tread blocks for Traction across Terrains:**

- Grooves in blocks helps in removal of soil and debris and better performance in tough & versatile terrains

**Strong & Durable carcass Ultra-durable casing with multiple steel belt layers and a strong hexagonal bead:**

- Offers exceptional puncture and impact resistance for demanding off-road applications.

**Reinforced shoulder design with an "Extra Protect Kurb Rib:**

- Shields the sidewall from cuts and abrasions, extending service life.

**Lightweight, Cut-Resistant Compound Special cut-resistant rubber formulation with reduced heat build-up:**

- Enhances maneuverability, improves fuel efficiency, and maintains durability in abrasive environments.



## Machineries



Motor Grader



Wheel Loader

**Standard:** ProductComponent.International Standards

## Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	17.5R25 (CR)
Rec Rim	14.00/1.5
Alternate Rim	-
PR & LI/SI	153A8/176A2 (* / *)
Section Width (mm)	445
Overall Diameter (mm)	1348
Static Load Radius (mm)	612
Rolling Circumference (mm)	4032
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

## Load Capacity

km/h / bar	3	5
10	-	7100
40	3650	-