



## EXB 380 - Technical Specifications

Industrial & Construction | Bias | E-2 | TT/TL | 5 Years



### Salient Features & Benefits

#### Excavator Bias 380, designed for excavator application

##### Superior Traction with Self-Cleaning Efficiency:

- Optimized Lug Angle.
- Delivers excellent grip on mixed terrains while efficiently shedding mud and debris, ensuring consistent performance in both dry and wet ground conditions.

##### Enhanced Vehicle Stability:

- Wider Tread Pattern.
- Offers a larger footprint for improved ground contact, enhancing balance and control, particularly useful during lifting or digging operations on uneven surfaces.

##### High Load-Carrying Strength with Durability:

- Strong Nylon Casing.
- Provides structural reinforcement for carrying heavy loads while offering resistance to impact, reducing the chances of tyre failure during tough operations.

## Machineries



Excavator

**Standard:** International Standards

### Dimensions International Standards

ECE	-
Tyre Size	400/70-20 (16.0/70-20)
Rec Rim	14
Alternate Rim	-
PR & LI/SI	18PR 165B
Section Width (mm)	417
Overall Diameter (mm)	1090
Static Load Radius (mm)	496
Rolling Circumference (mm)	3275
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	5.8
5	7210
10	6030
20	5820
25	5720
30	5670
40	5460
45	5250
50	5150
Static	10300