



MPB 400 - Technical Specifications

Industrial & Construction | Bias | MPT | TL | 5 Years



Salient Features & Benefits

Multi-Purpose Bias 400, designed for concrete mixer, telehandler & mini dumper applications.

Smooth Ride and Driving Comfort

- Wider Centre Lug.
- Minimizes vibrations and delivers a smoother, more comfortable driving experience across both paved and uneven terrain.

Reliable Grip in All Conditions

- Specially Designed Tread for Multi-Purpose Applications.
- Provides excellent traction and grip on- and off-road, ensuring reliable performance in field work, road transport, and municipal operations.

Enhanced Structural Durability

- Reinforced Carcass Construction.
- Carry's high load & provides resistance to puncture with extended tyre life, even in demanding multi-surface environments.

Machineries



Telehandler



Self Loading Concrete Mixer



Mini Dumper

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*7403*00
Tyre Size	10.0/75-15.3 (260/75-15.3)
Rec Rim	9
Alternate Rim	-
PR & LI/SI	18PR
Section Width (mm)	264
Overall Diameter (mm)	760
Static Load Radius (mm)	348
Rolling Circumference (mm)	2274
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Free Rolling

km/h / bar	7.1
10	3050
25	2590
30	2440
40	2180
50	1960

Drive Wheel

km/h / bar	7.1
10	2170
25	1840
30	1740
40	1550
50	1400