

## CLR 280 - Technical Specifications

Industrial & Construction | Radial | IND | TL | 7 Years

### Salient Features & Benefits

**Compact Loader Radial 280, specially designed for telehandlers and compact loaders in agro- industrial applications.**

#### Designed to combat the harsh operating conditions:

- Wider non-directional tread design.
- Provides outstanding Traction on any surface, including industrial applications on the harder surfaces.

#### Durability and Strength:

- Strong Nylon Casing with high-performance steel belts.
- Heavy load-carrying capacity with additional strength and protection.

#### Control & handling stability:

- Strong Sidewall.
- Outstanding stability in lift mode.

#### Reduced heat built up:

- Superior Cut & Chip Tread compound.
- Minimize cuts and punctures in heavy-duty loading applications, resulting in longer tyre life.

#### Excellent Driving Comfort:

- Larger Center Tread block.
- Smooth & comfortable ride as well as provides significant fuel savings.



## Machineries



Compact Loader

**Standard:** International Standards

### Dimensions International Standards

ECE	E11*106R00/20*7733*00
Tyre Size	405/70R18 (16.0/70R18) (SB)
Rec Rim	13
Alternate Rim	-
PR & LI/SI	141B/153A2
Section Width (mm)	407
Overall Diameter (mm)	1025
Static Load Radius (mm)	463
Rolling Circumference (mm)	3078
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	2	2.5	3	3.5	3.8
10	2130	2540	2960	3370	3650
20	1710	2040	2370	2700	2830
30	1640	1960	2280	2600	2730
40	1600	1910	2210	2520	2650
50	1550	1850	2150	2450	2575