



MPB 400 - Technical Specifications

Industrial & Construction | Bias | MPT | TL | 5 Years



Salient Features & Benefits

Multi-Purpose Bias 400, designed for concrete mixer, telehandler & mini dumper applications.

Smooth Ride and Driving Comfort

- Wider Centre Lug.
- Minimizes vibrations and delivers a smoother, more comfortable driving experience across both paved and uneven terrain.

Reliable Grip in All Conditions

- Specially Designed Tread for Multi-Purpose Applications.
- Provides excellent traction and grip on- and off-road, ensuring reliable performance in field work, road transport, and municipal operations.

Enhanced Structural Durability

- Reinforced Carcass Construction.
- Carry's high load & provides resistance to puncture with extended tyre life, even in demanding multi-surface environments.

Machineries



Telehandler



Self Loading Concrete Mixer



Mini Dumper

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*54R00/24*20031*00
Tyre Size	10.5-18
Rec Rim	9
Alternate Rim	-
PR & LI/SI	12PR 130G
Section Width (mm)	270
Overall Diameter (mm)	905
Static Load Radius (mm)	413
Rolling Circumference (mm)	2707
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Mixed Application

km/h / bar	4.5
15	3140
20	2850
30	2380
40	2190
50	2130
60	2090
70	2030
80	1980
90	1900