



MPB 400 - Technical Specifications

Industrial & Construction | Bias | MPT | TL | 5 Years



Salient Features & Benefits

Multi-Purpose Bias 400, designed for concrete mixer, telehandler & mini dumper applications.

Smooth Ride and Driving Comfort

- Wider Centre Lug.
- Minimizes vibrations and delivers a smoother, more comfortable driving experience across both paved and uneven terrain.

Reliable Grip in All Conditions

- Specially Designed Tread for Multi-Purpose Applications.
- Provides excellent traction and grip on- and off-road, ensuring reliable performance in field work, road transport, and municipal operations.

Enhanced Structural Durability

- Reinforced Carcass Construction.
- Carry's high load & provides resistance to puncture with extended tyre life, even in demanding multi-surface environments.

Machineries



Telehandler



Self Loading Concrete Mixer



Mini Dumper

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*8113
Tyre Size	12.0/75-18
Rec Rim	W9
Alternate Rim	11x18
PR & LI/SI	12PR
Section Width (mm)	298
Overall Diameter (mm)	915
Static Load Radius (mm)	417
Rolling Circumference (mm)	2737
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Free Rolling

km/h / bar	4
10	3400
25	2890
30	2720
40	2430
50	2190

Drive Wheel

km/h / bar	4
10	2380
25	2020
30	1900
40	1700
50	1530