



MPB 401 - Technical Specifications

Industrial & Construction | Bias | MPT | TL | 5 Years



Salient Features & Benefits

Multi-Purpose Bias 401, designed for telehandler & compact wheel loader applications.

Engineered for Versatile Applications

- Unique block Tread Design for Multi-Purpose Vehicles.
- Provides reliable traction and adaptability across a variety of on-road and off-road applications, ideal for municipal, agricultural, and industrial use.

Built for High-Speed and Harsh Conditions

- Reinforced Carcass with Specially-Formulated Compound.
- Ensures exceptional durability and performance in tough working environments, including high-speed operations, without compromising stability or safety.

Machineries



Telehandler



Compact Loader

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	-
Tyre Size	12.5-20
Rec Rim	11
Alternate Rim	-
PR & LI/SI	12PR 132G
Section Width (mm)	325
Overall Diameter (mm)	1040
Static Load Radius (mm)	473
Rolling Circumference (mm)	3110
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Mixed Application

km/h / bar	3.5
15	3300
20	3000
30	2500
40	2300
50	2240
60	2200
70	2140
80	2080
90	2000