



MPB 400 - Technical Specifications

Industrial & Construction | Bias | MPT | TL | 5 Years



Salient Features & Benefits

Multi-Purpose Bias 400, designed for concrete mixer, telehandler & mini dumper applications.

Smooth Ride and Driving Comfort

- Wider Centre Lug.
- Minimizes vibrations and delivers a smoother, more comfortable driving experience across both paved and uneven terrain.

Reliable Grip in All Conditions

- Specially Designed Tread for Multi-Purpose Applications.
- Provides excellent traction and grip on- and off-road, ensuring reliable performance in field work, road transport, and municipal operations.

Enhanced Structural Durability

- Reinforced Carcass Construction.
- Carry's high load & provides resistance to puncture with extended tyre life, even in demanding multi-surface environments.

Machineries



Telehandler



Self Loading Concrete Mixer



Mini Dumper

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*54R00/25*20035*00
Tyre Size	12.5-20
Rec Rim	11
Alternate Rim	-
PR & LI/SI	12PR 132G
Section Width (mm)	325
Overall Diameter (mm)	1040
Static Load Radius (mm)	473
Rolling Circumference (mm)	3110
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Mixed Application

km/h / bar	3.5
15	3300
20	3000
30	2500
40	2300
50	2240
60	2200
70	2140
80	2080
90	2000