

THB 230 - Technical Specifications

Agriculture | Bias | R-4/IND | TT/TL | 5 Years

Salient Features & Benefits

Telehandler Bias 230, specially designed for telehandlers

Excellent Traction and Self-Cleaning

- Specially-designed Directional Tread Pattern.
- Ensures superior traction and self-cleaning properties, providing excellent stability during vehicle operation.

Enhanced Durability

- Strong Nylon Carcass.
- Safeguards the tyre against structural failures, increasing overall reliability in demanding conditions.

Superior Driving Comfort

- Optimized tread and carcass design.
- Improves ride comfort even on uneven terrains.

Outstanding Ground Stability

- Robust tread structure and strong carcass.
- Provides high ground stability, reducing the risk of tipping and improving operational safety.

High Load-Carrying Capacity

- Reinforced nylon casing.
- Enables the tyre to handle heavy loads efficiently without compromising performance.

Exceptional Cut Resistance

- Durable rubber compound and heavy-duty construction.
- Resists cuts and punctures, reducing downtime and extending tyre life.



Machineries



Telehandler

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/18*6577*00
Tyre Size	405/70-20 (16.0/70-20)
Rec Rim	13
Alternate Rim	-
PR & LI/SI	14PR 149B
Section Width (mm)	418
Overall Diameter (mm)	1075
Static Load Radius (mm)	488
Rolling Circumference (mm)	3216
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar		3.5
30		3680
50		3250