

CLR 280 - Technical Specifications

Industrial & Construction | Radial | IND | TL | 7 Years

Salient Features & Benefits

Compact Loader Radial 280, specially designed for telehandlers and compact loaders in agro- industrial applications.

Designed to combat the harsh operating conditions:

- Wider non-directional tread design.
- Provides outstanding Traction on any surface, including industrial applications on the harder surfaces.

Durability and Strength:

- Strong Nylon Casing with high-performance steel belts.
- Heavy load-carrying capacity with additional strength and protection.

Control & handling stability:

- Strong Sidewall.
- Outstanding stability in lift mode.

Reduced heat built up:

- Superior Cut & Chip Tread compound.
- Minimize cuts and punctures in heavy-duty loading applications, resulting in longer tyre life.

Excellent Driving Comfort:

- Larger Center Tread block.
- Smooth & comfortable ride as well as provides significant fuel savings.



Machineries



Compact Loader

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/20*7734*00
Tyre Size	405/70R20 (16.0/70R20) (SB)
Rec Rim	13
Alternate Rim	-
PR & LI/SI	143B/155A2
Section Width (mm)	407
Overall Diameter (mm)	1076
Static Load Radius (mm)	488
Rolling Circumference (mm)	3231
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2	2.5	3	3.5	3.8
10	2320	2760	3200	3640	3875
20	1790	2130	2480	2820	3000
30	1730	2060	2390	2710	2890
40	1680	2000	2320	2640	2810
50	1630	1940	2250	2560	2725