

## THB 230 - Technical Specifications

Agriculture | Bias | R-4/IND | TT/TL | 5 Years

### Salient Features & Benefits

#### Telehandler Bias 230, specially designed for telehandlers

##### Excellent Traction and Self-Cleaning

- Specially-designed Directional Tread Pattern.
- Ensures superior traction and self-cleaning properties, providing excellent stability during vehicle operation.

##### Enhanced Durability

- Strong Nylon Carcass.
- Safeguards the tyre against structural failures, increasing overall reliability in demanding conditions.

##### Superior Driving Comfort

- Optimized tread and carcass design.
- Improves ride comfort even on uneven terrains.

##### Outstanding Ground Stability

- Robust tread structure and strong carcass.
- Provides high ground stability, reducing the risk of tipping and improving operational safety.

##### High Load-Carrying Capacity

- Reinforced nylon casing.
- Enables the tyre to handle heavy loads efficiently without compromising performance.

##### Exceptional Cut Resistance

- Durable rubber compound and heavy-duty construction.
- Resists cuts and punctures, reducing downtime and extending tyre life.



## Machineries



Telehandler

**Standard:** ProductComponent.International Standards

### Dimensions ProductComponent.International Standards

ECE	E11*106R00/18*6592*00
Tyre Size	405/70-24 (16.0/70-24)
Rec Rim	13
Alternate Rim	-
PR & LI/SI	14PR 152B
Section Width (mm)	418
Overall Diameter (mm)	1177
Static Load Radius (mm)	539
Rolling Circumference (mm)	3521
Type	TL

**Note:** Section Width And Overall Diameter Are Unloaded Dimensions.

### Load Capacity

km/h / bar	3.5
30	4020
50	3550