

CLR 280 - Technical Specifications

Industrial & Construction | Radial | IND | TL | 7 Years

Salient Features & Benefits

Compact Loader Radial 280, specially designed for telehandlers and compact loaders in agro- industrial applications.

Designed to combat the harsh operating conditions:

- Wider non-directional tread design.
- Provides outstanding Traction on any surface, including industrial applications on the harder surfaces.

Durability and Strength:

- Strong Nylon Casing with high-performance steel belts.
- Heavy load-carrying capacity with additional strength and protection.

Control & handling stability:

- Strong Sidewall.
- Outstanding stability in lift mode.

Reduced heat built up:

- Superior Cut & Chip Tread compound.
- Minimize cuts and punctures in heavy-duty loading applications, resulting in longer tyre life.

Excellent Driving Comfort:

- Larger Center Tread block.
- Smooth & comfortable ride as well as provides significant fuel savings.



Machineries



Compact Loader

Standard: International Standards

Dimensions International Standards

ECE	E11*106R00/21*11104*00
Tyre Size	365/80R20 (14.5R20) (SB)
Rec Rim	11
Alternate Rim	-
PR & LI/SI	141B/152A2
Section Width (mm)	360
Overall Diameter (mm)	1092
Static Load Radius (mm)	495
Rolling Circumference (mm)	3279
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

Load Capacity

km/h / bar	2	2.5	3	3.5	3.8
10	2190	2620	3030	3460	3650
20	1690	2020	2340	2670	2830
30	1630	1950	2260	2580	2730
40	1590	1900	2190	2500	2650
50	1540	1840	2130	2430	2575